

KNIPEX Quality – Made in Germany



KNIPEX CoBolt®

Compact and powerful

Available in 3 sizes:
6 1/4", 8" & 10"

Strong cutting edges;
especially hardened
and laser-cut

Gripping surface
for pulling wire

Lever-action for
high leverage cutting
in a small compact
sized tool





KNIPEX CoBolt® Compact Bolt Cutters

- ▶ Lever-action cutting for high leverage in a small compact sized tool
- ▶ Small, slim head for better access to confined areas
- > Compact and powerful tools that cuts bolts, nails, rivets, etc.
- > Heavy-duty, induction hardened edges for cutting thin, hard wire, screws and springs. Cutting edge hardness (approx. 64 HRC)
- > Less physical effort required due to efficient lever action mechanism
- > No slipping of the material being cut due to lasered cutting edge
- > Gripping surface below the joint for gripping and pulling wires
- > Chrome vanadium heavy-duty steel, forged, multi stage oil-hardened



71 01 160



71 02 200



71 22 200



71 01 250



Powerful cutting even at the tips of the blades



Slim head for easier accessibility



With notch in cutting edge to keep thicker round objects closer to the joint for easier cutting

| Part Number | Length | | Blade | Head | Pliers | Handles | Cutting Capacities | | | | | | | |
|---------------|--------|-----|----------|-----------|--------------------|----------------------|--------------------|------|--------|------|--------|------|--------|------|
| | inch | mm | | | | | Ø inch | Ø mm | Ø inch | Ø mm | Ø inch | Ø mm | Ø inch | Ø mm |
| 71 01 160 SBA | 6 1/4 | 160 | straight | straight | black atramentized | plastic coated | 13/64 | 5.3 | 11/64 | 4.4 | 1/8 | 3.0 | 1/8 | 3.0 |
| 71 31 160 SBA | 6 1/4 | 160 | notch | straight | black atramentized | plastic coated | 13/64 | 5.3 | 3/16 | 4.8 | 9/64 | 3.6 | 1/8 | 3.3 |
| 71 01 200 SBA | 8 | 200 | straight | straight | black atramentized | plastic coated | 1/4 | 6.0 | 13/64 | 5.2 | 5/32 | 4.0 | 9/64 | 3.6 |
| 71 02 200 SBA | 8 | 200 | straight | straight | black atramentized | slim multi-component | 1/4 | 6.0 | 13/64 | 5.2 | 5/32 | 4.0 | 9/64 | 3.6 |
| 71 12 200 SBA | 8 | 200 | straight | straight | black atramentized | slim multi-component | 1/4 | 6.0 | 13/64 | 5.2 | 5/32 | 4.0 | 9/64 | 3.6 |
| 71 21 200 SBA | 8 | 200 | straight | 20° angle | black atramentized | plastic coated | 1/4 | 6.0 | 13/64 | 5.2 | 5/32 | 4.0 | 9/64 | 3.6 |
| 71 22 200 SBA | 8 | 200 | straight | 20° angle | black atramentized | slim multi-component | 1/4 | 6.0 | 13/64 | 5.2 | 5/32 | 4.0 | 9/64 | 3.6 |
| 71 31 200 SBA | 8 | 200 | notch | straight | black atramentized | plastic coated | 1/4 | 6.0 | 13/64 | 5.2 | 5/32 | 4.0 | 9/64 | 3.6 |
| 71 41 200 SBA | 8 | 200 | notch | 20° angle | black atramentized | plastic coated | 1/4 | 6.0 | 13/64 | 5.2 | 5/32 | 4.0 | 9/64 | 3.6 |
| 71 01 250 SBA | 10 | 250 | straight | straight | black atramentized | plastic coated | - | - | 7/32 | 5.6 | 5/32 | 4.0 | 5/32 | 3.8 |
| 71 31 250 SBA | 10 | 250 | notch | straight | black atramentized | plastic coated | - | - | 1/4 | 6.0 | 11/64 | 4.3 | 11/64 | 4.2 |

KTIPEM2023