

KNIPEX Twistor® Crimpers

Powerful – compact – high capacity range

360° rotating crimping head

Square crimp profile on Twistor®16 version (97 53 18)




Trapezoidal crimp profile on Twistor® T version (97 53 19)

Crimping head can rotate 360° with 8 crimping positions

Easy crimping due to toggle lever transmission

Multi-component handles



KNIPEX Twistor® Crimpers

Self-adjusting crimping pliers for end sleeves (ferrules) with rotating crimp head

97

- ▶ Crimping head can be freely rotated 360°, with 8 crimping positions for a secure crimp in all positions
- ▶ Two crimp profiles available - square and trapezoid
- ▶ End sleeves (ferrules) can be crimped from almost any working position

- > Crimping pliers adjust automatically to different diameters
- > Crimp opening accessible from both sides, extra-long end sleeves can be fed in
- > Crimping of twin end sleeves (ferrules) up to 2 x 10 AWG (2 x 6 mm²)
- > Repetitive, high crimping quality due to integral lock (self-releasing mechanism)
- > Light and handy tool, manual force reinforced by toggle lever mechanism
- > Chrome vanadium electric steel in special quality, oil-hardened



97 53 18




97 53 19



Rotating crimping head for optimal accessibility, even in confined areas



Twin end sleeves (ferrules) up to 2 x 10 AWG (2 x 6 mm²) can be crimped without adjustment



Crimp end sleeve (ferrules) fully automatically within the capacity of each tool



Uniquely flexible: connectors can be inserted in the rotatable crimp head from almost any position



Part Number	Description	↔		Crimping Profile	Handles	Crimping Capacity mm ²	Crimping Capacity AWG	Number of crimping positions
		inch	mm					
97 53 18	KNIPEX Twistor®16	8	200		multi-component	0.14 - 16	26 - 6	8
97 53 19	KNIPEX Twistor® T	8	200		multi-component	0.14 - 10	26 - 8	8

New