

Pipe Wrenches S-Type

DIN 5234

83
3

- > slim, s-type jaw
- > jaws with offset teeth in opposite directions for a strong grip
- > induction hardened teeth for long life
- > three-point gripping on pipes, self-locking
- > i-beam handle design
- > captive adjusting nut
- > red powder-coated, jaws bright ground
- > chrome vanadium electric steel; forged, multi stage oil-hardened



83 30 015



| Product Number | Packaging | ↔ Inch mm | | Pliers | ⊗ Ø Inch Ø mm | ⊗ Inch | ⚖ lbs |
|----------------|-----------|-----------------|--|-------------------|---------------------|-----------|----------|
| 83 30 005 | | 9 1/2 245 | | red powder-coated | 1 3/8 35 | 1/2 | 1.04 |
| 83 30 010 | | 12 1/2 320 | | | 1 21/32 42 | 1 | 1.86 |
| 83 30 015 | | 16 1/2 420 | | | 2 3/64 60 | 1 1/2 | 3.31 |
| 83 30 020 | | 21 1/4 540 | | | 2 3/4 70 | 2 | 5.68 |
| 83 30 030 | | 26 3/4 680 | | | 4 3/4 120 | 3 | 9.33 |

Pipe Wrenches S-Type

with rapid adjustment

83
6

- > time-saving, precise adjustment of the opening width at the press of a button directly on the workpiece
- > less effort required due to self-locking action
- > no unintentional shifting of the pliers
- > pinch guard prevents operators' fingers being pinched
- > maximum load capacity due to completely hardened handles
- > high-wear resistance due to the induction hardened teeth
- > chrome vanadium electric steel; forged, multi stage oil-hardened



83 60 010



83 61 010



| Product Number | Packaging | ↔ Inch mm | | Pliers | Handles | ⊗ Ø Inch Ø mm | ⊗ Inch | ⚖ lbs |
|----------------|-----------|-----------------|--|--------------------|----------------|---------------------|-----------|----------|
| 83 60 010 | | 13 330 | | red powder-coated | | 1 21/32 42 | 1 | 1.96 |
| 83 60 015 | | 16 1/2 420 | | | | 2 3/64 60 | 1 1/2 | 3.30 |
| 83 61 010 | | 13 330 | | grey powder-coated | plastic coated | 1 21/32 42 | 1 | 2.11 |
| 83 61 015 | | 16 1/2 420 | | | | 2 3/64 60 | 1 1/2 | 3.24 |
| 83 61 020 | | 22 560 | | | | 2 3/4 70 | 2 | 5.47 |