Cable Shears

Short design, length only 20" (500 mm) Lightweight, high leverage

- > for cutting copper and aluminum cables, single and multi-stranded wire
- > not suitable for steel wire and wire ropes
- > precision ground, hardened blades
- > clean and smooth cut without crushing and deformation
- > less effort required due to favorable lever ratio and special blade geometry
- > pinch guard prevents operators' fingers being pinched
- > adjustable bolted joint
- > cutter head: vanadium electric steel, forged, oil-hardened
- > handle shank: aluminum tube, high-strength





Large cutting capacity: max. 1 1/16" (27 mm) dia. / 150 mm²

						Cutting capacities			
Product Number	Packaging	⊲- ► Inch mm		Head	Handles	Ø Inch Ø mm	mm ²	AWG	۲ Ibs
95 12 500		<mark>20</mark> 500	0 1	polished	multi-component grips	1 1/16 27	150	5/0	2.49
95 17 500		<mark>20</mark> 500	A 1000 V 🖄 🚭 🤂 📲 🕻	polished	plastic dipped insulated, VDE-tested	1 1/16 27	150	5/0	3.26

A 1000 V A 🕰 🖨 🛠 📲 🖫

Cable Shears

95

95

- > for cutting copper and aluminum cables, single and multi-stranded wire
- > not suitable for steel wire and wire ropes
- > precision ground, hardened blades
- > clean and smooth cut without crushing and deformation
- > favorable lever ratio due to toggle lever
- > pinch guard prevents operators' fingers being pinched
- > adjustable bolted joint
- > bolted cutter head, replaceable
- > blade head: high-grade chrome vanadium electric steel, forged, oil-hardened
- > handle: steel tube



					Cutting capacities			
Product Number Pac	kaging mr		Head	Handles	Ø Inch Ø mm	mm ²	AWG	۵'۵ Ibs
95 27 600	23 1 600	²	polished	plastic dipped insulated, VDE-tested	1 1/16 27	150	5/0	5.08