

# Screwdrivers for Hexagon Socket Screws

with T-Handle

IEC 60900 DIN EN 60900

98  
1

> special tool steel, oil-hardened



98 14 08  
⚠ 1000 V ○



98 15 08  
⚠ 1000 V ○



| Product Number | Packaging | ↔<br>Inch<br>mm |            | Width across flats S<br>mm | Length of non-insulated<br>blade ± 2<br>Inch<br>mm | T-Handle width<br>Inch<br>mm | ⚖<br>lbs |
|----------------|-----------|-----------------|------------|----------------------------|--|------------------------------|----------|
| 98 14 05       |           | 4 3/4<br>120    | ⚠ 1000 V ○ | 5.0                        | 23/64<br>9.0                                       | 3 1/2<br>90.0                | 0.49     |
| 98 14 06       |           | 4 3/4<br>120    |            | 6.0                        | 25/64<br>10.0                                      | 3 1/2<br>90.0                | 0.46     |
| 98 14 08       |           | 4 3/4<br>120    |            | 8.0                        | 7/16<br>11.0                                       | 3 1/2<br>90.0                | 0.63     |
| 98 15 05       |           | 10<br>250       | ⚠ 1000 V ○ | 5.0                        | 23/64<br>9.0                                       | 3 1/2<br>90.0                | 0.80     |
| 98 15 06       |           | 10<br>250       |            | 6.0                        | 25/64<br>10.0                                      | 3 1/2<br>90.0                | 1.00     |
| 98 15 08       |           | 10<br>250       |            | 8.0                        | 7/16<br>11.0                                       | 3 1/2<br>90.0                | 0.79     |

# T-handle

with driving square 3/8" or 1/2"

IEC 60900 DIN EN 60900

98  
40

- > for use with sockets
- > for quick, easy and secure locking of attached sockets
- > chrome plated
- > high-grade special tool steel; forged, oil-hardened



98 40  
⚠ 1000 V 1/2

| Product Number | Packaging | ↔<br>Inch<br>mm |              | Handle length<br>Inch<br>mm | Square drive<br>Inch | ⚖<br>lbs |
|----------------|-----------|-----------------|--------------|-----------------------------|----------------------|----------|
| 98 30          |           | 8<br>200        | ⚠ 1000 V 3/8 | 6 1/2<br>165                | 3/8                  | 0.91     |
| 98 40          |           | 8<br>200        | ⚠ 1000 V 1/2 | 6 1/2<br>165                | 1/2                  | 1.34     |